



Maximum Performance with the Compact Size Laser Projector

FEATURES

- Long lasting laser light source for constant brightness level and color performance for up to 20,000 hours maintenance free operations
- 6,000 lumens of brightness, WUXGA resolution, and 20,000:1 contrast ratio for clear, crisp and bright projection
- Great flexibility with 1.65x zoom lens and manual horizontal and vertical lens shift
- Image adjustment is made easy with 4 corner corrections, horizontal and vertical keystone corrections
- Built-in 2x 5W audio speakers with multiple audio interface to ensure your message is well heard
- HDBaseT interface for high definition video and audio transmission over 100 meters long cable
- DICOM Simulation Mode for medical training and seminars
- Compatible with NovoConnect Solution for wireless presentation and collaboration
- Eco friendly with automatic turning off function when there is no signal input for a period of time
- Compact size laser projector ideal for corporate meeting room



DU4771Z Laser Projector is Ideal for Corporate Meeting Room

With impressively vivid colors and a high brightness of 6,000 lumens, the DU4771Z offers the next generation of advanced laser light source technology. Designed lamp-free, it provides a low cost of ownership, with minimal maintenance, and gives a stable, high-quality projection for up to 20,000 hours. The DU4771Z offers an immersive big-screen experience with an unbeatable return on investment.



DU4771Z SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	6000 ANSI Lumens
	Native Resolution	WUXGA (1920 x 1200)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Contrast Ratio	20,000:1
	Native Aspect Ratio	16:10
	Keystone Correction	Vertical: +/-30°; Horizontal: +/-30°
Optical	Throw Ratio	1.15 - 1.90 : 1
	Image Size (Diagonal)	37" - 201"
	Projection Distance	1.5 - 5.0 m
	Projection Lens	F = 2.45 - 3.13, f = 17.23 - 27.9 mm
	Zoom Ratio	1.65x
	Offset	115% and Manual Lens Shift
	Lens Shift Range	Vertical: +12%; Horizontal: +/-2.5%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI Number of Ports v.1.4b (x3: HDMI/MHLx1, HDMiX2), Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45 (x2: HDBaseTx1, LANx1), RS-232, 3D-Sync (1: Out), USB A (Power Only), USB miniB (Service), Microphone (Mini-Jack)
General	Lamp Life and Type	Lamp free design. Laser light source lasts up to 20,000 hours
	Speakers	5W x 2
	Dimensions (W x D x H)	360 x 451.5 x 151 mm
	Weight	10.7 kg
	Noise Level	36dB/34dB (Normal/Eco. Mode)
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 350W (Eco. Mode), 430W (Normal Mode), <0.5W (Standby)
	Warranty	Large Venue Laser Phosphor Warranty: 5 Year projector / 5 years or 20.000h on the Laser Phosphor illumination source.(Whichever comes first)
	Standard Accessories	VGA Cable, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Remote Control P/N (5041846600)
	UPC Code	813097024138