

Epson EB-1930

DATASHEET



An ideal device for corporate or educational use, the EB-1930 is a great combination of quality output and features at an affordable price.

Convenient use

The Epson EB-1930 combines high-quality output, value-added features and affordability, into a compact and portable projector. It is perfect for corporate or educational use, as it can be easily installed in meeting rooms or used portably from a desktop.

High quality picture

Utilising Epson's 3LCD technology to ensure clearly projected images, the EB-1930 produces vivid, natural colours and an equally high White and Colour Light Output, even in daylight.

Connectivity

The EB-1930 boasts a DisplayPort connector, allowing you to show high definition audio and video content with ease.

Enhanced productivity

Productivity can be greatly increased with a range of features available with the EB-1930, such as Quick Corner.

KEY FEATURES

- 4,200 lumens White/Colour Light Output
- 3LCD technology for vivid colours
- Program projector actions in advance
- Read PDFs directly from a USB stick



EPSON[®]
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.63 inch with MLA (D7)

IMAGE

Color Light Output	4,200 lumen - 2,730 lumen (economy)
White Light Output	4,200 lumen - 2,730 lumen (economy)
Resolution	XGA, 1024 x 768, 4:3
Contrast Ratio	3,000 : 1
Lamp	215 W, 3,500 h durability, 5,000 h durability (economy mode)
Keystone Correction	Auto vertical: $\pm 30^\circ$, Manual horizontal $\pm 30^\circ$
Video Processing	10 Bits

OPTICAL

Projection Ratio	1.38 - 2.24:1
Zoom	Manual, Factor: 10, 16
Projection Lens Zoom Ratio	1 - 1.6 : 1
Lens	Optical
Projection Size	30 inches - 300 inches
Projection Distance Wide	0.8 m - 8.4 m (60 inch screen)
Projection Distance Tele	1.4 m - 13.9 m (60 inch screen)
Projection Lens F Number	1.51 - 1.99
Focal Distance	18 m - 29 m
Focus	Manual
Offset	8.6 : 1

CONNECTIVITY

USB Display Function	3 in 1: Image / Mouse / Sound
Interfaces	USB 2.0 Type B, USB 2.0 Type A, RS-232C, HDMI in, RGB out, Stereo mini jack audio out, RGB in (2x), Stereo mini jack audio in (2x), Ethernet interface (100 Base-TX / 10 Base-T), 10 Base-T, VGA in (2x), VGA out, Composite in
Smartphone Connection	Yes with Epson iOS App

ADVANCED FEATURES

Security	Kensington lock, Security bar, Control panel lock, Password lock
2D Colour Modes	Dynamic
Features	AV Mute Slide, Automatic input selection, Automatic keystone correction, Direct Power on/off, Document Camera Compatible, Freeze image, Instant on/off, JPEG Viewer, Network administration, PC Free, Quick Corner, Slide show, Split-Screen-Function
Video Color Modes	Dynamic, Theatre, Blackboard, Photo, Presentation, sRGB, Whiteboard, DICOM SIM
Video Compatibility	NTSC, NTSC 4.43, PAL, M-PAL, N-PAL, PAL-60, SECAM, SECAM up to 1080i, SECAM up to 1080p, 480i, 480p, 526i, 526p, 720i, 720p, 1080i, 1080p

GENERAL

Energy Use	298 W, 212 W (economy), 0.44 W (standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Dimensions	377 mm x 108 mm x 271 mm (Width x Depth x Height)
Weight	3.7 kg
Noise Level	Normal: 37 dB (A) - Economy: 29 dB (A)
Temperature	Operation 5°C - 35°C , Storage -10°C - 60°C
Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection, EasyMP Slide Converter
Options	Air filter ELPAF38
Sound Pressure	Operation: 37 dB (A)-standby: 29 dB (A)
Loudspeaker	10 W

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Software (CD)
- User manual
- User manual (CD)
- Remote control incl. batteries

LOGISTICS INFORMATION

- SKU
V11H506041
- Barcode
8715946517155
- Dimensions Single Carton
517 x 342 x 196 mm
- Weight
5.51 Kg



For more information please contact:

Telephone: 0871 222 6702 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740

Web: www.epson.co.uk
www.epson.ie

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.