

Proyector brillante, compacto y fácil de utilizar con bajo coste total de propiedad

PT-LW376

Diseñado para aplicaciones en entornos empresariales y educativos. LCD, 3600 lúmenes, proyector WXGA.



KEY FEATURES

- LCD, 3600 lúmenes, WXGA
- Ciclo de sustitución de la lámpara de hasta 20.000 horas (menor coste total de propiedad)
- Funcionamiento silencioso para disfrutar de una proyección sin distracciones
- Proyección inalámbrica (opcional)
- Relación de contraste de 16.000:1

SPECIFICATIONS

Dimensions (W x H x D)	335 x 96*5 x 252 mm (13 3/16" x 3 25/32" *5 x 9 29/32")
Power Consumption	300 W
Lens	Manual zoom (1.2x), manual focus lens, F = 1.6–1.76, f = 19.16–23.02 mm, throw ratio: 1.48–1.78:1
Resolución	1280 x 800 pixels
Operating Environment	Operating temperature*7: Normal use: 5–40 °C (41–104 °F) at altitudes less than 1,400 m (4,593 ft); 5–35 °C (41–95 °F) at altitudes of 1,400–2,700 m (4,593–8,858 ft); Operating humidity: 20–80 % (No condensation)

Keystone Correction Range

Vertical: ±35 ° (Auto, Manual), Horizontal: ±35 ° (Manual)

Instalación	Ceiling/desk, front/rear
Cabinet Materials	Molded plastic
Applicable Software	Multi Monitoring & Control Software, Early Warning Software, Logo Transfer Software, Presenter Light Software (for Windows®)*8, Wireless Projector for iOS/Android™*9
Power Supply	AC 100–240 V, 50/60 Hz
Light Source	230 W x 1 lamp
Terminals LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, PjLink™ (Class 2) compatible
Screen size [diagonal]	0.76–7.62 m (30–300 in), 16:10 aspect ratio
Note	*1 Availability may vary by country or region. *2 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *3 Lamp replacement cycle stated is maximum value, at which time brightness will have decreased to 50 %. Usage environment affects lamp replacement cycle. *4 ET-WML100 Series and AJ-WM50 Series devices are both compatible with supported projectors in this series, and either can be used to enable the wireless network function. *5 With legs at shortest position. *6 Average value. May differ depending on the actual unit. *7 When [LAMP POWER] is set to [NORMAL] and the projector is operated at an elevation of 1,400 m (4,593 ft) or less, if the ambient temperature exceeds 35 °C (95 °F), [LAMP POWER] will be switched to [ECO] automatically to protect the projector. When [LAMP POWER] is set to [NORMAL] and the projector is operated at an elevation between 1,400 m (4,593 ft) and 2,700 m (8,858 ft), if the ambient temperature exceeds 30 °C (86 °F), [LAMP POWER] will be switched to [ECO] automatically to protect the projector. *8 When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted. *9 When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).
Terminals Computer 1 In	D-sub HD 15-pin (female) x 1 [RGB/YBPBR/YC]
Terminals Video In	Pin jack x 1
Terminals Audio In 1	M3 (L,R) x 1
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compatible)
Terminals Audio Out	M3 (L,R) x 1 (Variable)
Terminals Computer 2 In/1 Out	D-sub HD 15-pin (female) x 1 [RGB/YBPBR] (Input/output switching)
LCD Panel Panel Size	15.0 mm (0.59 in) diagonal (16:10 aspect ratio)
LCD Panel Number of pixels	1,024,000 (1280 x 800 pixels) x 3
Built in Speaker	10 W monaural
Terminals Audio In 2	Pin jack x 2 (L,R)
Filter Replacement Cycle	Normal: 5,000 h/Eco: 6,000 h/Quiet: 10,000 h
Terminals USB B	-
Terminals USB A	USB Type-A (for Memory Viewer/Wireless Module [ET-WML100/AJ-WM50 series*4]/Power supply [DC 5 V/2 A])
Operation Noise*2	Normal: 38 dB, Eco: 35 dB, Quiet: 30 dB
Weight*6	Approx. 2.9 kg (6.4 lbs)
Light Output *2	3,600 lm
Contrast Ratio*2	20,000:1 (All white/all black, Iris: On, Image mode: Dynamic, Auto Power Save: Off, Daylight View: Off, Lamp control: Normal)
Terminals HDMI 1/2 IN	HDMI 19-pin x 2 (Compatible with HDCP 1.4, Deep Color), Audio signal: Linear PCM (Sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
Center-to-corner zone ratio*2	85 %
Lamp replacement cycle*3	Normal: 10,000 h/Eco: 20,000 h/Quiet: 10,000 h
Light output	3,600 lm

CONTACT

Web: <https://business.panasonic.es/sistemas-visuales/contact-us>